



Type		HJW3-1600	HJW3-2500	HJW3-4000	HJW3-6300	
Rated current (A)	In	200、400、630、800、1000、1100、1600	630、800、1000、1250、1600、2000、2500	2500、2900、3150、3200、3600、3900、4000	5000、6300	
Rated service voltage (V)	Ue	AC400V、690V	AC400V、690V	AC400V、690V	AC400V、690V	
Rated insulation voltage (V)	Ui	1000V	1000V	1000V	1000V	
Rated impulse withstand voltage (kV)	Uimp	12	12	12	12	
Number of poles	P	3、4	3、4	3、4	3、4	
Rated current for N pole (A)		100%In	100%In	100%In	50%In	
Rated ultimate short-circuit breaking capacity (kA)	Icu	400V	55	80	100	120
		690V	30	50	65	75
Rated operation short-circuit breaking	Ics	400V	50	80	80	100
		690V	25	40	65	65
Rated short-circuit withstand current (kA)	Icw	400V	50	55	80	100
		690V	25	40	50	65
Breaking time (ms)		<30				
Closing time (ms)		<70				
Life (C/O period)	Mechanism	15000	15000	10000	5000	
	Electric	8000	8000	7000	1500	
Overall dimension : H×W×D (mm)	Draw out -type	3P	345×275×3045	433×375×390	433×435×390	433×895×390
		4P	345×275×3045	433×470×390	433×550×390	433×895×390
	Fixed-type	3P	310×262×2285	402×368×290	402×462×290	/
		4P	310×332×2285	402×463×290	402×541×290	/